

- GRIP RANGE: .027 .165 HOLE SIZE: .375 +.004/-.000 A/F AFTER ALL APPLIED FINISHES. INSTALLED LENGTH: 1.015 MAX. 2.
- 3.
- 4.
- 5.
- INSTALLED THREAD DEPTH: .945 REF. LUBRICATION: OIL INSTALLATION TOOL: SSG 802 SPIN SPIN

REVISIONS								
REV.	DESCRIPTION	DATE	ECN					
Α	NEW RELEASE	2/27/07						
В	NEW FINISH PER SFS-01-001, SC2	1/21/15	1745					

PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON- TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.	APPLI	CATION	DO NOT SCALE DRAWING	1 42. 7 10-075-0550			SCALE: 2:1	:1 WEIGHT:.0104 kg SHEET 1 OF			T 1 OF 1	
	NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2 WWW.shere Phone: 866		vww.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			AH2-2520-165B			В	
	THIS DRAWING. AND THE INFORMATION CON-			C1008/C1010	COMMENTS: E-mail: info@sherex.com		SIZE DWG. NO. REV					
	PROPRIETARY AND CONFIDENTIAL			MATERIAL	Q.A.							
				TOLERANCING PER: ASME Y14.5M-1994	MFG APPR.	AJP	2/27/07	HALF HEX LARGE FLANGE				
			TOLERANCES: ANGULAR: MACH±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002	ENG APPR.	TOO	2/27/07	TITLE:					
				CHECKED			TITLE.					
				DRAWN	TOO	2/27/07						
				UNLESS OTHERWISE SPECIFIED:		NAME	DATE					
517	ALLATION TOOL: 55G 80	DZ SPIN SPIN					В '`	SC2		1/21/	15	1745