A INITIAL	RELEASE 10/17/14	1707		.511 MAX A/F 3/8-16 UNC 2B PER ASME B1.1			I	.025 .995
	Ø.762 .734			A/F				
				3/8-16 UNC 2B PER ASMF B1.1				
				MINOR DIA.: .307	7321—			
NOTE: 1. GRIP R/	ANGE: .177295							
 HOLE SI INSTALL 	IZE: .512 +.004/000 A ED LENGTH: .689 REF. ATION: NONE	A/F AFTER ALL ·	_ APPLIED FIN	NISHES.			SEC	TION A-A
5. INSTALL	ATION TOOL: FLEX 5F PROOF LOAD MEET	9/5S SPIN PUL S GRADE 5 PI	L ER SAE J995:	10,300LBF				
				UNLESS OTHERWISE SPECIFIED:	:	NAME	DATE	
	_			DIMENSIONS ARE IN INCHES	DRAWN		10/17/14	
				TOLERANCES: ANGULAR: MACH ± 1 BEND ±1 TWO PLACE DECIMAL ±.01	CHECKED			
				THREE PLACE DECIMAL ±.005	ENG APPR.	JVK	10/17/14	TITLE:
	-			TOLERANCING PER: ASME Y14.5M-1994	MFG APPR.			LARGE FLANGE FULL HEX
	PROPRIETARY AND CONFIDENTIAL			MATERIAL	Q.A.	JR	10/17/14	
	T NOT RELAKT AND CONFIDENTIAL			C1008/C1010	COMMENTS:	Ochar		SIZE DWG. NO.
THI	S DRAWING, AND THE INFORMATION CON-			ED ON CHROMATE PER SHEREX SFS-01-001 Phone		nail: info@sherex.com w.sherex.com one: 866-474-3739 : 716-875-0358		
TAI ANE TO SHE	S DRAWING, AND THE INFORMATION CON- VED HERN, ARE THE PROPERTY OF SHEREX ARE NOT TO BE USED IN ANY MANNER DETRIMENT THE INTEREST OF THE COMPANY. REX SOLUTIONS RESERVES THE RIGHT TO REVISE TRDRAWING WITHOUT NOTICE.	NEXT ASSY	USED ON	CHROMATE PER SHEREX SFS-01-001	Filone. 800		-	A FHL2-3716-295 A