

-3/8-24 UNF 2B PER ASME B1.1 MINOR DIA.: .330-.340


SECTION A-A



1. GRIP RANGE: .150 - .312

- 2. HOLE SIZE: .531 +.006/-.000 AFTER ALL APPLIED FINISHES.
- 3. INSTALLED LENGTH: .425 MAX.
- 4. LUBRICATION: WAX

5. INSTALLATION TOOL: SSG 803 SPIN SPIN



	000 31 11 4 31 11			1	
			UNLESS OTHERWISE SPECIFIED:		
PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON- TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX RESERVES THE RIGHT TO REVISE			DIMENSIONS ARE IN INCHES		
			TOLERANCES:  ANGULAR: MACH±1 BEND±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005  INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	DRAWN	
				CHECKED	
				ENG APPR.	
				MFG APPR.	
				Q.A.	
				COMMENTS	
			MATERIAL C1008/C1010	E-mail: in	
	NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2	Phone: 8 Fax: 716-	
PART/DRAWING WITHOUT NOTICE.	APPLICATION		DO NOT SCALE DRAWING		

:				
		NAME	DATE	
	DRAWN	TOO	5/23/05	
	CHECKED			T
	ENG APPR.	TOO	5/23/05	
	MFG APPR.	AJP	5/23/05	
	Q.A.			
	COMMENTS:			

MENTS:

E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358

TITLE:

SMALL FLANGE OPEN END

SIZE DWG. NO. CAK2-3724-312

SCALE: 2:1 | WEIGHT: .0088 kg | SHEET 1 OF 1

5

1

3

2

1

**REV** 

В