





NOTE:

- 1. GRIP RANGE: .027 .165
- 2. HOLE SIZE: .391 +.006/-.000 AFTER ALL APPLIED FINISHES.
- 3. INSTALLED LENGTH: .380 MAX.
- 4. LUBRICATION: NONE
- 5. INSTALLATION TOOL: MS 50 SPIN PULL

SECTION A-A

ZONE	REV.	DESCRIPTION	DATE	APPROVED	
	Α	NEW RELEASE	5/23/05	TOO	
	В	ECN 1053	10/16/2007	TOO	

						В	ECN 105	53 10/16/2	2007	TOO
			UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ± 1 TWO PLACE DECIMAL ± .001 THREE PLACE DECIMAL ± .002 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994 MATERIAL 302/303 STAINLESS	DRAWN	пам					
				CHECKED			TITLE:			
				ENG APPR.	TO	5/23/05	11166.			
				MFG APPR.	AJF	5/23/05	LARGE FLANGE OPEN END			
DDODDIETADY AND CONFIDENTIAL				Q.A.						
PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON-				COMMENTS:						
TAINED HERIN ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY.			FINICI	E-mail: info@sherex.com		SIZE DWG. NO.		REV		
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE			FINISH PASSIVATE	www.sherex.com			▲ CAL1-2528-165		В	
PART/DRAWING WITHOUT NOTICE.	NEXT ASSY USED ON	TAGGIVATE	Phone: 866-474-3739 Fax: 716-875-0358			A 37 12 2020 100				
	APPLICATION		DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT:.0046 kg	SHEE	T 1 OF 1	

5

4

3

2

1