

NOTE:

GRIP RANGE: 0.7 - 4.2

HOLE SIZE: 10.00 +0.15/-0.0 AFTER ALL APPLIED FINISHES. 2.

3. INSTALLED LENGTH: 9.65 MAX.

LUBRICATION: NONE

4. 5. INST

REVISIONS										
ZONE	REV.	DESCRIPTION	DATE	APPROVED						
	Α	NEW RELEASE	7/20/05	TOO						
	В	ECN 1053	10/16/2007	TOO						

STALLATION TOOL: MS 50 SPIN PULL						В		EC	CN 1053 10/16/200		T	00	
				UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN METRIC TOLERANCES:	DRAW	'N	NAME TOO	DATE 7/20/05					
				ANGULAR: MACH ± 1 BEND ±1 ONE PLACE DECIMAL ±.5 TWO PLACE DECIMAL ±.25	CHEC	KED			TITI C.				
				INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG A	PPR.	TOO	7/20/05	LABOR ELANOR OBENIEND				
THIS DRAWING, AND THE INFORMATION CON- TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY.			MFG A		APPR.	AJP	7/20/05						
	TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT			MATERIAL 302/303 STAINLESS	Q.A.								
					COMMENTS: E-mail: info@sherex.com			com	SIZE DWG. NO. REV				
	SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE	NEXT ASSY	USED ON	FINISH PASSIVATE	www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		39	A C	CAL1-610-4.2				
	APPLI	APPLICATION DO NOT SCALE DRAWING		1 ux. 7 10-075-05		0000	000	SCALE: 2:1	VEIGHT:.0044 kg	SHEE	T 1 OF 1		
	4												

5

3

2