

- INSTALLED LENGTH: .425 MAX. 3.
- 4. LUBRICATION: WAX
- INSTALLATION TOOL: SSG 803 SPIN SPIN

_									
			UNLESS OTHERWISE SPECIFIED:		NAME	DATE		_	
PROPRIETARY AND CONFIDENTIAL THIS DEAVING, AND THE INFORMATION CON- TAINED HERRY NÆET THE PROPERTY OF SKEEEX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.			DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	DRAWN	TOO	11/3/06	TITLE:		
				CHECKED					
				ENG APPR.	TOO	11/3/06	IIILE.		
				MFG APPR.	AJP	11/3/06	LARGE FLANGE OPEN END		
			MATERIAL	Q.A.					
			C1008/1010	COMMENTS:		SIZE DWG. NO. REV			
			FINISH	E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358				REV	
	NEXT ASSY	USED ON	ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2			A C	AL2-3124-312	2 B	
	APPLICATION		DO NOT SCALE DRAWING	1 4 7 10 010 0000			SCALE: 2:1	WEIGHT:.0104 kg	SHEET 1 OF
5	4		3		2		1		