


**NOTE:**

1. GRIP RANGE: .020 - .130
2. HOLE SIZE: .297 +.006/.000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: .315 MAX.
4. LUBRICATION: WAX
5. INSTALLATION TOOL: SSG 802 SPIN SPIN

**PROPRIETARY AND CONFIDENTIAL**  
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.  
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE		
		DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .002 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		DRAWN	TOO		
		MATERIAL		ENG APPR.	TOO	7/20/05	<b>TITLE:</b> LARGE FLANGE OPEN END
		A5056		MFG APPR.	AJP	7/20/05	
		FINISH		Q.A.			<b>SIZE DWG. NO.</b> <b>A</b> CAL3-1032-130
		NONE		<b>COMMENTS:</b> E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			
NEXT ASSY	USED ON						<b>REV</b> A
APPLICATION		DO NOT SCALE DRAWING					<b>SCALE: 2:1</b> WEIGHT: .0008 kg. <b>SHEET 1 OF 1</b>