




Unified Thread (Unit – Inches)

Part Number (steel)	Thread Size	Grip Range Min. Max.	L ±.015	HD ±.010	HT ±.003	D Max.	IL Max.	HOLE SIZE +.006/–.000
CA02-1032-130	10-32 UNF	.020 .130	.440	.320	.020	.280	.330	.281



CAO Specifications
Material: Steel 1008/1010

Part Number Description
CA02-1032-130

Finish: Zinc Plated
per ASTM B633 Fe/Zn 8, Type III

CAO
Product Style
Low Profile
Smooth Shank
Thin Wall Series

2
Material
2-Steel

1032
Thread Size

130
Grip Range

(-)
Empty-Open End
B-Closed End

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX FASTENING SOLUTIONS AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

NOTE: SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

SHEREX FASTENING SOLUTIONS

1400 COMMERCE PKWY.
LANCASTER, NY 14086 USA



SHEREX FASTENING SOLUTIONS

DRAWN BY:

DATE:

SCALE:

TITLE:

JLA

8/11/03

1:1

CAO RIVET NUT, OPEN END

CHECK'D BY:

DATE:

E-mail: info@sherex.com
www.sherex.com

DRAWING NO.

APPR'D BY:

DATE:

Phone: 866-474-3739
Fax: 716-681-0270

CA02-1032-130

REV

DESCRIPTION

ECN

DATE

AJP