




REVISIONS				
REV	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	08/21/2025	4672	MRA



M5X0.8 6H
 PER ASME B1.13M
 MINOR DIA.: 4.14 - 4.33




SECTION A-A
 SCALE 4 : 1

- NOTE:
- GRIP RANGE: 0.5 - 3.0
 - HOLE SIZE: 7.0+0.1/-0.0 A/F AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 9.0 REF.
 - LUBRICATION: NONE
 - INSTALLATION TOOL: FLEX 5P/5S SPIN PULL

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.
 UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.3 TWO PLACE DECIMAL ± 0.08	DRAWN	MRA	8/21/25
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED		
		MATERIAL	ENG APPR.	JVK	8/21/25
		1010 STEEL	MFG APPR.		
			Q.A.		
			COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		
NEXT ASSY	USED ON	FINISH ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4			
APPLICATION		DO NOT SCALE DRAWING			



TITLE:
 SMALL FLANGE FULL HEX

SIZE	DWG. NO.	REV
A	CFKM2-580-3.0	A
SCALE: 2:1		WEIGHT:
SHEET 1 OF 1		