




REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INTIITAL RELEASE	06/02/26	4759	JH



M12X1.75 6H
 PER ASME B1.13M
 MINOR DIAM.: 10.11 - 10.44



SECTION A-A

- NOTE:
- GRIP RANGE: 1.0-4.0
 - HOLE SIZE: 16.0 A/F +0.1/-0.0 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 16 REF
 - LUBRICATION: NONE
 - INSTALLATION TOOL: SPIN PULL

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE			
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	JH	1/15/26			
			CHECKED					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.					
		MATERIAL 1010 Steel	MFG APPR.					
			Q.A.			TITLE: LARGE FLANGE FULL HEX		
			COMMENTS:					
			E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358					
		FINISH ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4				SIZE A	DWG. NO. CFLM2-12175-4.0	REV A
NEXT ASSY	USED ON							
APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1 WEIGHT: SHEET 1 OF 1		