



REVISIONS			
REV.	DESCRIPTION	DATE	ECN
A	INITIAL RELEASE	5/18/09	1184



NOTE:

- GRIP RANGE: 0.76 min.
- HOLE SIZE:
 - 0.76 - 2.29 MT'L THICK.: 7.14 AFTER ALL APPLIED FINISHES.
 - 2.31 - 3.15 MT'L THICK.: 7.36 AFTER ALL APPLIED FINISHES.
 - 3.17 - 4.72 MT'L THICK.: 7.36 AFTER ALL APPLIED FINISHES.
 - 4.72 - OVER MT'L THICK.: 7.54 AFTER ALL APPLIED FINISHES.
- INSTALLED LENGTH: N/A
- LUBRICATION: NONE
- INSTALLATION TOOL: SSG 802 SPIN SPIN

SECTION A-A



PROPRIETARY AND CONFIDENTIAL
THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE			
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH± 1 BEND ±1 ONE PLACE DECIMAL ±0.10 TWO PLACE DECIMAL ±0.05	DRAWN	TWR	5/18/09			
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED					
		MATERIAL	ENG APPR.	JVK	5/18/09			
		304L STAINLESS	MFG APPR.					
		FINISH	Q.A.	JVK	5/18/09	TITLE: CADMIUM FREE SMALL FLANGE SWAGING		
		TIN ALLOY PER ASTM B545	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358					
NEXT ASSY	USED ON							
APPLICATION		DO NOT SCALE DRAWING	SIZE DWG. NO.			REV		
			A CFT1-580			A		
			SCALE: 2:1 WEIGHT: kg			SHEET 1 OF 1		