


NOTE:

1. GRIP RANGE: .062 MIN.
2. HOLE SIZE: .297 +.005/-.000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: N/A
4. LUBRICATION: NONE
5. INSTALLATION TOOL: SSG 802 SPIN SPIN

SECTION A-A

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:	NAME	DATE
		DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002	DRAWN	JLA 8/11/03
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED	
		MATERIAL	ENG APPR.	JLA 8/11/03
		12L14	MFG APPR.	AJP 8/11/03
		FINISH	Q.A.	
		TIN ALLOY PER ASTM B545	COMMENTS:	
NEXT ASSY	USED ON	DO NOT SCALE DRAWING	E-mail: info@sherex.com	
			www.sherex.com	
			Phone: 866-474-3739	
			Fax: 716-875-0358	

		
TITLE:		
CADMIUM FREE KNURLED BODY SWAGING		
SIZE	DWG. NO.	REV
A	CFW2-1024	A
SCALE: 2:1	WEIGHT: .0013 kg	SHEET 1 OF 1