


NOTE:

1. GRIP RANGE: .062 MIN.
2. HOLE SIZE: .594 +.005/-.000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: N/A
4. LUBRICATION: NONE
5. INSTALLATION TOOL: SSG 803 SPIN SPIN

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
		DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		DRAWN	JLA	
		MATERIAL		CHECKED		
		12L14		ENG APPR.	JLA	8/11/03
		FINISH		MFG APPR.	AJP	8/11/03
NEXT ASSY	USED ON	TIN ALLOY PER ASTM B545		Q.A.		
APPLICATION		DO NOT SCALE DRAWING		COMMENTS:		TITLE: CADMIUM FREE KNURLED BODY SWAGING
				E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		
				SIZE	DWG. NO.	REV
				A	CFW2-3716	A
				SCALE: 2:1	WEIGHT: .0101 kg	SHEET 1 OF 1