


SECTION A-A

- NOTE:**
1. GRIP RANGE: 1.57 MIN.
  2. HOLE SIZE: 9.92 +0.13/-0.0 AFTER ALL APPLIED FINISHES.
  3. INSTALLED LENGTH: N/A
  4. LUBRICATION: NONE
  5. INSTALLATION TOOL: SSG 802 SPIN SPIN

**PROPRIETARY AND CONFIDENTIAL**  
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.  
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.10 TWO PLACE DECIMAL ± 0.05		DRAWN	JLA	
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		CHECKED		
		MATERIAL		ENG APPR.	JLA	8/11/03
		12L14		MFG APPR.	AJP	8/11/03
		FINISH		Q.A.		
		TIN ALLOY PER PER ASTM B545		COMMENTS:		<b>TITLE:</b> <b>CADMIUM FREE KNURLED BODY SWAGING</b>
NEXT ASSY		USED ON		E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		
APPLICATION		DO NOT SCALE DRAWING		SIZE DWG. NO.		REV
				<b>A</b> CFW2-610		<b>A</b>
				SCALE: 2:1 WEIGHT: .0033 kg		SHEET 1 OF 1