




REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	03/05/2026	4782	MRA



M3X0.5 6H
 PER ASME B1.13M
 MINOR DIA.: 2.46 - 2.60



SECTION A-A

- NOTE:
- GRIP RANGE: 0.5 - 2.0
 - HOLE SIZE: 5.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 6.3 REF
 - LUBRICATION: NONE
 - INSTALLATION TOOL: SPIN PULL

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	MRA	3/5/26	TITLE: SMALL FLANGE SEMI HEX			
			CHECKED						
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.	JVK	3/5/26				
			MFG APPR.						
		MATERIAL 1010 Steel	Q.A.						
		FINISH ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358			SIZE A	DWG. NO. CHKM2-350-2.0	REV A	
NEXT ASSY	USED ON					SCALE: 2:1			
APPLICATION		DO NOT SCALE DRAWING				WEIGHT:		SHEET 1 OF 1	