




REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	04/01/26	4792	JH



- NOTE:
- GRIP RANGE: 1.5-4.5
 - HOLE SIZE: 16.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 21.1 REF
 - LUBRICATION: NONE
 - INSTALLATION TOOL: SPIN PULL

SECTION A-A

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE		
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH: ± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	JH	1/14/26		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED			TITLE: SMALL FLANGE KNURLED BODY	
			ENG APPR.	JK	15/5/26		
		MFG APPR.					
		MATERIAL	Q.A.				
		1010 STEEL	COMMENTS:			SIZE DWG. NO. REV A CKKM2-12175-4.5B A	
		FINISH	E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358				
		ZINC WITH CLEAR TRIVELANT CHROMATE PER SFS-01-001, SC4					
NEXT ASSY	USED ON						
APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1 WEIGHT: SHEET 1 OF 1	