





REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	3/26/26	4791	JLC



- NOTE:
- GRIP RANGE: 1.5-3.0
 - HOLE SIZE: 5.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 5.4 REF
 - LUBRICATION: NONE
 - INSTALLATION TOOL: SPIN PULL
 - COUNTERSUNK HOLE DEPTH: 1.2 MAX



HOLE DETAIL



SECTION A-A

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.
UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.3 TWO PLACE DECIMAL ± 0.08		DRAWN	JLC	
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		CHECKED		
		MATERIAL 1010 STEEL		ENG APPR.	JVK	
		FINISH ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4		MFG APPR.		TITLE: COUNTERSUNK HEAD SMOOTH
				Q.A.		
				COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		SIZE DWG. NO. A COCM2-350-3.0
						REV A
						SCALE: 6:1 WEIGHT: SHEET 1 OF 1

5

4

3

2

1