




REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	03/26/26	4791	JLC




SEE NOTE 6



NOTE:

- GRIP RANGE: 3.5 - 5.0
- HOLE SIZE: 6.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
- INSTALLED LENGTH: 5.9 REF
- LUBRICATION: NONE
- INSTALLATION TOOL: SPIN PULL
- COUNTERSUNK HOLE DEPTH: 1.2 MAX



PROPRIETARY AND CONFIDENTIAL
THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.
UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:	NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.3 TWO PLACE DECIMAL ± 0.08	DRAWN	JLC 3/26/26
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED	
		MATERIAL 1010 STEEL	ENG APPR.	JVK 3/26/26
			MFG APPR.	
			Q.A.	
			COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358	
NEXT ASSY	USED ON	FINISH ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4		
APPLICATION		DO NOT SCALE DRAWING		

		
TITLE: COUNTERSUNK HEAD SMOOTH		
SIZE A	DWG. NO. COCM2-470-5.0	REV A
SCALE: 5:1 WEIGHT:		SHEET 1 OF 1