



REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	3/31/26	4791	JLC



SEE NOTE 6





NOTE:

- GRIP RANGE: 1.5-4.0
- HOLE SIZE: 7.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
- INSTALLED LENGTH: 14.0 REF
- LUBRICATION: NONE
- INSTALLATION TOOL: SPIN PULL
- COUNTERSUNK HOLE DEPTH: 1.2 MAX

NOTE 2

HOLE DETAIL



SECTION A-A

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	JLC	3/31/26
			CHECKED		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.	JVK	3/31/26
			MFG APPR.		
		MATERIAL	Q.A.		
		1010 STEEL	COMMENTS:		
			E-mail: info@sherex.com		
		FINISH	www.sherex.com		
		ZINC WITH CLEAR TRIVALENT CHROMATE PER SFS-01-001, SC4	Phone: 866-474-3739		
NEXT ASSY	USED ON		Fax: 716-875-0358		
APPLICATION		DO NOT SCALE DRAWING			



TITLE:

COUNTERSUNK HEAD SMOOTH

SIZE DWG. NO.

A COCM2-580-4.0B

REV

A

SCALE: 5:1 WEIGHT:

SHEET 1 OF 1