







PER ASME B1.1 MINOR DIA .: .145 - .156

#10-24 UNC 2B

SECTION A-A

NOTE:

GRIP RANGE: .020 - .175

- HOLE SIZE: .336 +.006/-.000 AFTER ALL APPLIED FINISHES. 2.
- INSTALLED LENGTH: .410 REF. LUBRICATION: WAX 3.

4.

5. INSTAL

RICATION: WAX ALLATION TOOL: SSG 8	02 SPIN SPIN										
			UNLESS OTHERWISE SPECIFIED:								
			DIMENSIONS ARE IN INCHES		NAME	DATE					
			TOLERANCES: ANGULAR: MACH±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	TOO	7/20/05					
				CHECKED			TITLE:				
				ENG APPR.	TOO	7/20/05	PRE-BULBED SLOTTED BODY			NDV	
				MFG APPR.	AJP	7/20/05				זטנ	
			TOLERANCING PER: ASME Y14.5M-1994	Q.A.							
PROPRIETARY AND CONFIDENTIAL			ASME 114.5M-1994	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358							
THIS DRAWING, AND THE INFORMATION CON- TAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY. SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.			MATERIAL C1008/C1010				SIZE DWG			REV	
	NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2				A CPB2-1024-175			В	
FAKI/DKAWING WIINOUI NOIICE.	APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1	WEIGHT: .0047 kg	HT: .0047 kg SHEET 1 OF 1		