


Unified Thread (Unit – Inches)

Part Number (steel)	Thread Size	Grip Range Min. Max.	L ±.015	HD ±.015	HT ±.005	D Max.	IL Ref.	HOLE SIZE +.006/–.000
CPB2–3118–280	5/16–UNC	.020 .280	1.141	.755	.062	.492	.570	.500



CPB Specifications
Material: Steel 1008/1010

Part Number Description

CPB2–3118–280

Finish: Zinc Plated–Yellow Dichromate
per ASTM B633 Fe/Zn 8, Type II

CPB
Product Style
Slotted Body
Pre–bulbed

2
Material
2–Steel

3118
Thread Size

280
Grip Range

THIS DRAWING, AND THE INFORMATION CONTAINED HERIN, ARE THE PROPERTY OF SHEREX FASTENING SOLUTIONS. AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

NOTE: SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

SHEREX FASTENING SOLUTIONS

1400 COMMERCE PKWY.
LANCASTER, NY 14086 USA



DRAWN BY:	DATE:	SCALE:	TITLE:
TOO	5/23/05	1:1	CPB STYLE RIVET NUT

CHECK'D BY:	DATE:
TOO	5/23/05

E–mail: info@sherex.com
www.sherex.com

Phone: 866–474–3739
Fax: 716–681–0270

DRAWING NO.

CPB2–3118–280

REV	DESCRIPTION	ECN	DATE
-----	-------------	-----	------