

REVISIONS									
REV.	DESCRIPTION	DATE	ECN						
Α	INITIAL RELEASE	10/17/14	1707						








5/16-18 UNC 2B PER ASME B1.1

MINOR DIA .: .252 - .265



SECTION A-A

NOTE:

- GRIP RANGE: .031 .157
- HOLE SIZE: .433 +.004/-.000 A/F AFTER ALL APPLIED FINISHES. INSTALLED LENGTH: .535 REF. 2.
- 3.
- 4. LUBRICATION: NONE
- INSTALLATION TOOL: FLEX 5P/5S SPIN PULL 5.
- THREAD PROOF LOAD MEETS GRADE 5 PER SAE J995: 6,950LBF

				•							
				UNLESS OTHERWISE SPECIFIED:		NAME	DATE		_		
	PROPRIETARY AND CONFIDENTIAL THIS DRAWING, AND THE INFORMATION CON- TAINED HERINI ARE THE PROPERTY OF SHEREX, AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT			DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994 MATERIAL C1008/C1010 FINISH	DRAWN	MJK	10/17/14	27			
					CHECKED						
					ENG APPR.	JVK	10/17/14	TITLE:			
					MFG APPR.			LARG	X		
		-			Q.A.	JR	10/17/14				
					COMMENTS: E-mail: info@sherex.com		SIZE DWG. NO. REV				
	TO THE INTEREST OF THE COMPANY. SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE				www.sherex.com		A FHL2-3118-157		A		
	PART/DRAWING WITHOUT NOTICE.	NEXT ASSY	USED ON	ZINC PLATE CLEAR TRIVALENT CHROMATE PER SHEREX SFS-01-001	Phone: 866-474-3739 Fax: 716-875-0358			A 111L2-3110-137			
		APPLICATION		DO NOT SCALE DRAWING	1 ax. 7 10-07 0-000		SCALE: 2:	1 WEIGHT:	SHEE	ET 1 OF	
	4								T		

3

2