


REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIALS
A	INITIAL RELEASE	9/4/24	4528	PMZ



- NOTE:
- GRIP RANGE: 3.0 - 5.0
 - HOLE SIZE: 13.00 +0.15/-0.00 A/F AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 20.50 MAX
 - LUBRICATION: NONE
 - INSTALLATION TOOL: FLEX 18/RIV 943 SPIN PULL
 - THREAD MEETS CLASS 10 PROOF LOAD PER ISO 898-2: 60.3kN


PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.3 TWO PLACE DECIMAL ± 0.08	DRAWN	PMZ	9/4/24
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED		
			ENG APPR.	JVK	9/4/24
		MATERIAL 10B21	MFG APPR.	AP	9/4/24
			Q.A.		
		FINISH ZINC PLATE CLEAR TRIVALENT CHROMATE PER SHEREX SFS-01-001 SC1	COMMENTS:		
			E-mail: info@sherex.com		
NEXT ASSY	USED ON		www.sherex.com		
			Phone: 866-474-3739		
APPLICATION		DO NOT SCALE DRAWING	Fax: 716-875-0358		

		
TITLE: FULL HEX HIGH STRENGTH		
SIZE	DWG. NO.	REV
A	HHS2-1015-5.0	A
SCALE: 2:1		WEIGHT:
		SHEET 1 OF 1