


REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIALS
A	INITIAL RELEASE	8/22/24	4523	PMZ



- NOTE:
- GRIP RANGE: 3.0 - 5.0
  - HOLE SIZE: 16.66 +0.15/-0.00 A/F AFTER ALL APPLIED FINISHES.
  - INSTALLED LENGTH: 25.00 MAX
  - LUBRICATION: NONE
  - INSTALLATION TOOL: FLEX18 SPIN-PULL
  - THREAD MEETS CLASS 10 PROOF LOAD: 88.5kN PER ISO 898-2

**PROPRIETARY AND CONFIDENTIAL**

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	PMZ	8/22/24
			CHECKED		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.	JVK	8/22/24
			MFG APPR.		
		MATERIAL	Q.A.		
		10B21	COMMENTS:		
			E-mail: info@sherex.com		
			www.sherex.com		
			Phone: 866-474-3739		
			Fax: 716-875-0358		
		FINISH			
		ZINC PLATE CLEAR TRIVALENT CHROMATE PER SHEREX SFS-01-001 SC1			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			



TITLE:  
FULL HEX HIGH STRENGTH

SIZE	DWG. NO.	REV
<b>A</b>	HHS2-12175-5.0	A
SCALE: 3:2	WEIGHT:	SHEET 1 OF 1