


REVISIONS				
REV.	DESCRIPTION	DATE	ECN	INITIAL
A	INITIAL RELEASE	6/3/2025	4665	EAK



- NOTE:
- GRIP RANGE: 5.5-7.5
 - HOLE SIZE: 17.45 +.15/-0.00 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH:
 - LUBRICATION: NONE
 - INSTALLATION TOOL: SPIN PULL
 - THREADS MEET CLASS 10 PROOF LOAD PER ISO 898-2 - 88.5 kN


PROPRIETARY AND CONFIDENTIAL

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.

SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED, ALL SPECIFICATIONS REFERENCED ON THIS DRAWING WILL PERTAIN TO THE MOST RECENT AND ACTIVE REVISION.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ±1 ONE PLACE DECIMAL ±0.3 TWO PLACE DECIMAL ±0.08	DRAWN	EAK	6/3/25
			CHECKED		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	ENG APPR.	JVK	6/3/25
			MFG APPR.		
		MATERIAL	Q.A.		
		10B21 STEEL	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		
		FINISH			
		ZINC PLATE CLEAR TRIVALENT CHROMATE PER SHEREX SFS-01-001, SC1			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			



TITLE:
HIGH STRENGTH ROUND BODY M12

SIZE DWG. NO. REV
A RHS2-12175-7.5 **A**

SCALE: 2:1 WEIGHT: .036KG SHEET 1 OF 1