


SECTION A-A

- NOTE:**
1. GRIP RANGE: 1.0 - 4.0
 2. HOLE SIZE: 16.0 +0.1/-0.0 AFTER ALL APPLIED FINISHES.
 3. INSTALLED LENGTH: N/A
 4. INSTALLED THREAD DEPTH:
 5. LUBRICATION: NONE
 6. INSTALLATION TOOL: MS 100 SPIN PULL

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.10 TWO PLACE DECIMAL ± 0.05	DRAWN	JVK	3/5/08
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED		
		MATERIAL	ENG APPR.	JVK	3/5/08
		ALUMINUM ALMG 2.5 DIN 3.3523	MFG APPR.	TB	8/7/08
		FINISH NONE	Q.A.		
NEXT ASSY	USED ON		COMMENTS:		
			E-mail: info@sherex.com		
			www.sherex.com		
			Phone: 866-474-3739		
			Fax: 716-875-0358		
APPLICATION		DO NOT SCALE DRAWING			

			TITLE:		
			FLAT HEAD OPEN END		
SIZE	DWG. NO.	REV			
A	TU-AM12UPO40	A			
SCALE: 2:1	WEIGHT: .0071 kg	SHEET 1 OF 1			